



## OAK CHEVRON GREY

The distinctive, weathered grey stain on this ready-to-install, patterned oak board from the Chevron Collection brings an elegant expression to this traditional floor, and accentuates its timeless look. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Partial handcrafting gives each board its unique appearance, while micro-bevelling enhances the iconic geometric design.

Left version

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES			
<b>Article Number</b>	151XADEKWKKW18L	<b>Wood Species</b>	Oak	<b>Moisture content</b>	EN13183	7%±2%	
<b>Surface treatment</b>	Oil	<b>Board</b>	Pattern	<b>Minimum Mean Density kg/m<sup>3</sup></b>		>500 kg/m <sup>3</sup>	
<b>Design features</b>	Bevelled 4-sided, brushed	<b>Grading</b>	Lively (Country)	<b>Reaction To Fire</b>	EN13501-1	Dfl-s1	
<b>Dimensions</b>	1848 x 305 x 15 mm	<b>Range</b>	Kährs ID	<b>Formaldehyde Emission</b>	EN717-1	E1	
<b>Weight per Package</b>	20.01 kg	<b>Collection</b>	Chevron Collection	<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n	
<b>Status in Movex</b>	20	<b>Resandable</b>	2-3 times	<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD	
<b>Area per Package</b>	2.04 m <sup>2</sup>	<b>Natural/Stained</b>	Stained	<b>Thermal Conductivity</b>	EN12664	0,14 W/mK	
<b>Area Per Board</b>	0.51 m <sup>2</sup>	<b>Brinell Value</b>	3, 7	<b>Thermal Resistance R-Value</b>		.11 (m2K/W)	
<b>DETAIL DESCRIPTION</b>	Naturally occurring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers.		<b>Joint</b>	Tongue & Groove	<b>Biological Durability</b>	EN350-2	Class 1
<b>COLOUR CHANGE</b>	Stained product - noticable color change over time.		<b>Floor heating</b>	Yes	<b>CARB2</b>		Compliant
		<b>Warranty</b>	30 years	<b>Wear-layer material</b>	Hardwood		
		<b>Wear-layer thickness</b>	3, 5 mm	<b>Core material</b>	Poplar		
		<b>Backside material</b>	Oak	<b>Thickness</b>	15 mm		
		<b>Installation method</b>	Glue-down	<b>EAN Code</b>	7393969041935		
		<b>Surface Colour</b>	Grey				

### CERTIFICATES

